

Technical Information

Model			Econic 9	Econic 12	Econic 18
Product Code			GRAE09B932- GRAE09K932 KSZKLM660	GRAE12B932- GRAE12K932 KSZKLM661	GRAE18B932- GRAE18K932 KSZKLM662
Power Supply	Rated Voltage	V ~	220 ~ 240	220 ~ 240	220 ~ 240
	Rated Frequency	Hz	50	50	50
	Phases	Ph	1	1	1
Power Supply Mode			Outdoor	Outdoor	Outdoor
Cooling Capacity		W	2580 (980 ~ 2900)	3500 (1100 ~ 3700)	5275 (1200 ~ 5500)
Heating Capacity		W	2700 (680 ~ 3000)	3500 (1100 ~ 3800)	5375 (1370 ~ 6100)
Cooling Power Input		W	800 (300 ~ 900)	1090 (340 ~ 1150)	1650 (370 ~ 2000)
Heating Power Input		W	750 (190 ~ 830)	970 (300 ~ 1060)	1490 (350 ~ 1700)
Cooling Power Current		A	3,6 (1,3 - 4,5)	4,8 (1,5 - 5,4)	7,3 (1,7 - 9,3)
Heating Power Current		A	3,4 (0,9 - 4,0)	4,3 (1,3 - 5,0)	7,1 (1,6 - 8,0)
Rated Input		W	1600	1900	2900
Rated Current		A	8	9,5	12
SEER		W/W	6,50	6,65	6,57
SCOP		W/W	4,37	4,36	4,02
Indoor Unit	Model of Indoor Unit		Econic 9	Econic 12	Econic 18
	Indoor Unit Product Code		GRAE09B932	GRAE12B932	GRAE18B932
	Dimension (WXHxD)	mm	750 x 285 x 200	750 x 285 x 200	900 x 310 x 225
	Net Weight	kg	7,5	8	12
Outdoor Unit	Outdoor Unit Model		Econic 9	Econic 12	Econic 18
	Outdoor Unit Product Code		GRAE09K932	GRAE12K932	GRAE18K932
	Dimension (WXHxD)	mm	730 x 545 x 285	730 x 545 x 285	800 x 545 x 315
	Net Weight	kg	26	26	35
	Refrigerant		R32	R32	R32
	Refrigerant Charge	kg	0,58	0,68	1,28
Connection Pipe	Outer Diameter Liquid Pipe	mm	6,35	6,35	6,35
	Outer Diameter Gas Pipe	mm	9,52	9,52	12
	Max Distance Height	m	7	7	10
	Max Distance Length	m	10	10	15