

Technical Information

Model			Kazettás 12	Kazettás 18	Kazettás 24
Product Code			GRA12CAB932-GRA12CAK932 KSZKLM613	GRA18CAB932-GRA18CAK932 KSZKLM614	GRA24CAB932-GRA24CAK932 KSZKLM615
Power Supply	Rated Voltage	V ~	220 ~ 240	220 ~ 240	220 ~ 240
	Rated Frequency	Hz	50	50	50
	Phases	Ph	1	1	1
Power Supply Mode			Outdoor	Outdoor	Outdoor
Cooling Capacity		W	3600 (1350 ~ 4400)	5000 (1530 ~ 5600)	7000 (2160 ~ 8200)
Heating Capacity		W	4200 (1240 ~ 5300)	5600 (1400 ~ 6200)	8000 (1980 ~ 9300)
Cooling Power Input		W	1080 (260 - 1600)	1630 (470 - 2300)	2180 (670 - 3560)
Heating Power Input		W	1230 (190 - 1510)	1730 (460 - 2250)	2100 (650 - 3620)
Cooling Power Current		A	4,74 (1,1 ~ 5,76)	7,16 (2,25 ~ 10,1)	9,57 (3,21 ~ 15,63)
Heating Power Current		A	5,40 (0,78 ~ 6,6)	7,60 (2,2 ~ 9,88)	9,22 (3,11 ~ 15,9)
Rated Input		W	890	1075	2085
Rated Current		A	6,05	7,10	9,50
SEER		W/W	6,20	6,40	6,50
SCOP		W/W	4,10	4,00	4,20
Indoor Unit	Model of Indoor Unit		Kazettás 12	Kazettás 18	Kazettás 24
	Indoor Unit Product Code		GRA12CAB932	GRA18CAB932	GRA24CAB932
	Dimension (WXHxD)	mm	570 x 570 x 260	570 x 570 x 260	835 x 835 x 250
	Net Weight	kg	17	17	24
Panel	Dimension (WXHxD)	mm	650 x 650 x 55	650 x 650 x 55	950 x 950 x 55
	Dimension of Package (WXHxD)	mm	710 x 710 x 80	710 x 710 x 80	1000 x 1000 x 100
	Net Weight	kg	2,2	2,2	5,3
	Gross Weight	kg	3,7	3,7	7,8
Outdoor Unit	Outdoor Unit Model		Kazettás 12	Kazettás 18	Kazettás 24
	Outdoor Unit Product Code		GRA12CAK932	GRA18CAK932	GRA24CAK932
	Dimension (WXHxD)	mm	800 x 315 x 545	800 x 315 x 545	900 x 350 x 700
	Dimension of Package (WXHxD)	mm	920 x 400 x 620	920 x 400 x 620	1020 x 430 x 770
	Net Weight	kg	35	37	51
	Refrigerant		R32	R32	R32
	Refrigerant Charge	kg	0,9	1,16	1,4
Connection Pipe	Outer Diameter Liquid Pipe	mm	6,35	6,35	9,52
	Outer Diameter Gas Pipe	mm	12,7	12,7	15,88
	Max Distance Height	m	10	20	25
	Max Distance Length	m	25	30	50